



# RECESSED / GIMBAL DOWNLIGHT

RDT / GDT series



Circadian Lighting

+



Tunable White

## RDT series



### FEATURES 產品特點

- Circadian rhythm of light 2800K - 5700K during different time
- Dual Colours - Single point source LED
- Available in 5W – 30W for 25W – 150W halogen equivalent
- Tunable white and dimmable to 5%
- Selectable CCT - 2800K/3000K/3500K/4000K/4500K/5000K/5700K
- Transformer 100-240V 50/60Hz input (Sold separately)
- Android apps or optional 2.4GHz Wireless Remote Control
- Honeycomb louver accessory available
- 不同時間的晝夜節律燈光2800K - 5700K
- 雙色 - 單點光源 LED
- 5W – 30W燈具電源可選 · 相當於 25W – 150W 鹵素燈
- 可調白光及可調光至 5%
- 可選色溫 - 2800K/3000K/3500K/4000K/4500K/5000K/5700K
- 變壓器 100-240V 50/60Hz 輸入 ( 單獨出售 )
- Android 應用程序或可選的 2.4GHz 無線遙控器
- 可提供蜂窩板配件

### APPLICATIONS 應用

- Display, Hotel, Office, Residential, Restaurant, Retail, Speciality
- 展示、酒店、辦公室、住宅、餐廳、零售、其他

### PRODUCT INFORMATION 產品資料

Colour temp.:	2800K – 5700K
色溫:	
CRI :	90 (Typ.) CRI 80 and 95 on request
顯色指數:	
Color Consistency:	3 Steps MacAdam @2800K and @5700K
顏色一致性:	
Selectable CCT:	2800K / 3000K / 3500K / 4000K / 4500K / 5000K / 5700K
可選 CCT :	
Brightness Setting:	100% / 75% / 50% / 25% / 10% / 5%
亮度設置:	
Beam Angle:	15° / 24° / 38° / 60°
光束角:	
Mode: A-Mode (Auto - CCT changing – Constant power 自動 - 色溫變化 - 恆定功率)	
模式: C-Mode (Circadian Rhythm - CCT-brightness changing 晝夜節律 - 色溫亮度變化)	

\*CCT selection and Dimming functions by remote control or Android Apps  
通過遙控器或 Android 應用程序選擇 CCT 和調光功能

\*\*For informational purposes only. Content is subject to change  
僅供參考。內容可能會需要更改。

# RDT series



Model No. 型號	Ceiling cut-out (mm) 開孔直徑	Outer diameter (mm) 外徑	Height (mm) 高度	Max. wattage (W) 最大瓦數	Lumen output (lm)* 輸出流明
RDT75	Ø75-80	Ø90	70	10W	502 – 588 lm
RDT95	Ø95-100	Ø108	85	20W	1092 – 1277 lm
RDT125	Ø125-130	Ø135	97	30W	1638 – 1916 lm

Lumen output with different wattage PSU (Power supply unit)  
不同瓦數電源下的流明輸出

Model No. 型號	5W	10W	15W	20W	30W	40W
RDT75	286 – 334 lm	502 – 588 lm	N.A.	N.A.	N.A.	N.A.
RDT95	320 – 374 lm	621 – 727 lm	875 – 1024 lm	1092 – 1277 lm	N.A.	N.A.
RDT125	333 – 389 lm	640 – 749 lm	932 – 1090 lm	1197 – 1401 lm	1638 – 1916 lm	N.A.

\*Lumen output at CCT2800K–CCT5700K. Data for reference only.

\*CCT2800K–CCT5700K 下的流明輸出。數據僅供參考。

## ORDERING INFORMATION 訂購資料

Example Model 示例: RDT95-WT-BK-38D-928-957

RDT	95	-	WT	-	BK	-	38D	-	928 - 957
Series 系列	Ceiling cut-out Diameter 開孔直徑	-	Body colour 鋁殼顏色	-	Reflector colour 反光罩顏色	-	Beam angle 光束角	-	CCT range 相對色溫範圍
RDT	75 Ø75-80mm (Max. 10W)		WT White 白色		WT White 白色		15D (15°)		928 – 957 2800K – 5700K@90 CRI *(CRI 80 / 95 on request)
	95 Ø95-100mm (Max. 20W)				BK Black 黑色		24D (24°)		
	125 Ø125-130mm (Max. 30W)						38D (38°)		
							60D (60°)		

\*For informational purposes only. Content is subject to change.  
僅供參考。內容可能會更改。

\*\*PSU is sold separately 電源單獨訂購